



| REV.   | REVISIONS REC.   |  | DATE:   | REV.          | REVISIONS REC.      |             | DATE:                        |
|--|------------------|--|---|---------------|---------------------|-------------|------------------------------|
| 0  |                  |  |   | 2             |                     |             |                              |
| 1  |                  |  |   | 3             |                     |             |                              |
| DRAWN & DRAFTED BY   | <b>XIAO ZHUO</b> |  | TOLERANCES  | ANGLE:        | TITLE:              |             |                              |
| CHECKED & APPROVED BY  | <b>YI YING</b>   |  | $0 < L \leq 4 \pm 0.1$<br>$4 < L \leq 16 \pm 0.2$<br>$16 < L \leq 83 \pm 0.3$ | $\pm 1^\circ$ | BOBBIN PQ-2625(12P) |             |                              |
|  |                  |  | pin pitch $\pm 0.2$   | UNIT:         | BOBBIN MATERIAL:    | PHENOLIC    | UL REG. UL 94V-0             |
|  |                  |  |   | SCALE:        | PIN MATERIAL:       | CP WIRE     | PIN TENSION LOAD: 1.2kg MIN. |
| <b>YUXIANG Magnetic Materials Ind. Co., Ltd.</b><br>TEL:006-592-2217130 FAX:006-592-222216 |                  |  |   |               | DATE:               | DRAWING NO. | REV.                         |
|  |                  |  |   |               | JUN 30 2004         | FX-2602     | 1                            |